


ENC@SS INOX 2RS



For Extremely **HUMID** Environments

CHOOSE OUR



SILVER BOX



The **color**
bearings company

Tel.: (+34) 937 541 674 • www.brلبearings.com • brل@brلبearings.com

Code	Inner diameter (d)	Diameter (D)	Width (B)	Weight	Speed Revs/min	Static Charge Kn
6000 2RS ENC INOX	10	26	8	20	20.000	1,61
6001 2RS ENC INOX	12	28	8	25	16.750	1,93
6002 2RS ENC INOX	15	32	9	30	15.500	2,33
6003 2RS ENC INOX	17	35	10	40	14.500	2,66
6004 2RS ENC INOX	20	42	12	69	13.000	4,09
6005 2RS ENC INOX	25	47	12	80	11.000	4,79
6006 2RS ENC INOX	30	55	13	120	8.750	6,55
6007 2RS ENC INOX	35	62	14	160	7.200	8,51
6008 2RS ENC INOX	40	68	15	190	6.500	9,66
6009 2RS ENC INOX	45	75	16	250	5.900	11,70
6010 2RS ENC INOX	50	80	16	260	5.600	12,77
6011 2RS ENC INOX	55	90	18	390	4.900	17,35
6012 2RS ENC INOX	60	95	18	420	4.500	18,93
6013 2RS ENC INOX	65	100	18	440	4.250	20,46
6014 2RS ENC INOX	70	110	20	600	4.000	25,78
6015 2RS ENC INOX	75	115	20	640	3.650	27,83

Code	Inner diameter (d)	Diameter (D)	Width (B)	Weight	Speed Revs/min	Static Charge Kn
6200 2RS ENC INOX	10	30	9	36	17.120	2,13
6201 2RS ENC INOX	12	32	10	41	14.338	2,54
6202 2RS ENC INOX	15	35	11	49	13.268	3,07
6203 2RS ENC INOX	17	40	12	69	12.412	3,89
6204 2RS ENC INOX	20	47	14	150	11.128	5,36
6205 2RS ENC INOX	25	52	15	170	9.416	6,55
6206 2RS ENC INOX	30	62	16	240	7.490	9,17
6207 2RS ENC INOX	35	72	17	330	6.163	12,52
6208 2RS ENC INOX	40	80	18	410	5.564	14,73
6209 2RS ENC INOX	45	85	19	460	5.050	16,70
6210 2RS ENC INOX	50	90	20	500	4.794	19,64
6211 2RS ENC INOX	55	100	21	650	4.194	23,73
6212 2RS ENC INOX	60	110	22	820	3.852	29,46
6213 2RS ENC INOX	65	120	23	990	3.638	33,96
6214 2RS ENC INOX	70	125	24	1040	3.424	36,01
6215 2RS ENC INOX	75	130	25	1210	3.124	40,10

Code	Inner diameter (d)	Diameter (D)	Width (B)	Weight	Speed Revs/min	Static Charge Kn
6300 2RS ENC INOX	10	35	11	57	14.250	2,82
6301 2RS ENC INOX	12	37	12	64	12.900	3,40
6302 2RS ENC INOX	15	42	13	86	11.600	4,42
6303 2RS ENC INOX	17	47	14	160	10.300	5,67
6304 2RS ENC INOX	20	52	15	180	9.050	6,96
6305 2RS ENC INOX	25	62	17	270	7.100	9,33
6306 2RS ENC INOX	30	72	19	390	6.100	13,34
6307 2RS ENC INOX	25	80	21	500	5.550	15,55
6308 2RS ENC INOX	40	90	23	670	4.900	20,46
6309 2RS ENC INOX	45	100	25	870	4.300	26,19
6310 2RS ENC INOX	50	110	27	1090	3.950	31,10
6311 2RS ENC INOX	55	124	29	1390	3.425	38,87
6312 2RS ENC INOX	60	130	31	1740	3.250	42,56
6313 2RS ENC INOX	65	140	33	2100	2.990	49,10
6314 2RS ENC INOX	70	150	35	2500	2.825	57,49
6315 2RS ENC INOX	75	160	37	3000	1.600	62,61

2RS



ENC  SS

 TECHNICAL CHARACTERISTICS

- Stainless steel
- Standard radial play
- Rubber 2rs shields
- Lubricated

 FIELDS OF USE

- Applications with a high level of humidity

