

ENC@SS INOX 2RS



Para entornos de **HUMEDAD** extrema

ELIGE LA



SILVER BOX



The color
bearings company

Tel.: (+34) 937 541 674 • www.brllbearings.com • brl@brllbearings.com

| Código | Agujero (B) | Diámetro (D) | Ancho (W) | Peso g | Velocidad Rotaciones/min. | Carga Estática Kn |
|-------------------|-------------|--------------|-----------|--------|---------------------------|-------------------|
| 6000 2RS ENC INOX | 10 | 26 | 8 | 20 | 20.000 | 1,61 |
| 6001 2RS ENC INOX | 12 | 28 | 8 | 25 | 16.750 | 1,93 |
| 6002 2RS ENC INOX | 15 | 32 | 9 | 30 | 15.500 | 2,33 |
| 6003 2RS ENC INOX | 17 | 35 | 10 | 40 | 14.500 | 2,66 |
| 6004 2RS ENC INOX | 20 | 42 | 12 | 69 | 13.000 | 4,09 |
| 6005 2RS ENC INOX | 25 | 47 | 12 | 80 | 11.000 | 4,79 |
| 6006 2RS ENC INOX | 30 | 55 | 13 | 120 | 8.750 | 6,55 |
| 6007 2RS ENC INOX | 35 | 62 | 14 | 160 | 7.200 | 8,51 |
| 6008 2RS ENC INOX | 40 | 68 | 15 | 190 | 6.500 | 9,66 |
| 6009 2RS ENC INOX | 45 | 75 | 16 | 250 | 5.900 | 11,70 |
| 6010 2RS ENC INOX | 50 | 80 | 16 | 260 | 5.600 | 12,77 |
| 6011 2RS ENC INOX | 55 | 90 | 18 | 390 | 4.900 | 17,35 |
| 6012 2RS ENC INOX | 60 | 95 | 18 | 420 | 4.500 | 18,93 |
| 6013 2RS ENC INOX | 65 | 100 | 18 | 440 | 4.250 | 20,46 |
| 6014 2RS ENC INOX | 70 | 110 | 20 | 600 | 4.000 | 25,78 |
| 6015 2RS ENC INOX | 75 | 115 | 20 | 640 | 3.650 | 27,83 |

| Código | Agujero (B) | Diámetro (D) | Ancho (W) | Peso g | Velocidad Rotaciones/min. | Carga Estática Kn |
|-------------------|-------------|--------------|-----------|--------|---------------------------|-------------------|
| 6200 2RS ENC INOX | 10 | 30 | 9 | 36 | 17.120 | 2,13 |
| 6201 2RS ENC INOX | 12 | 32 | 10 | 41 | 14.338 | 2,54 |
| 6202 2RS ENC INOX | 15 | 35 | 11 | 49 | 13.268 | 3,07 |
| 6203 2RS ENC INOX | 17 | 40 | 12 | 69 | 12.412 | 3,89 |
| 6204 2RS ENC INOX | 20 | 47 | 14 | 150 | 11.128 | 5,36 |
| 6205 2RS ENC INOX | 25 | 52 | 15 | 170 | 9.416 | 6,55 |
| 6206 2RS ENC INOX | 30 | 62 | 16 | 240 | 7.490 | 9,17 |
| 6207 2RS ENC INOX | 35 | 72 | 17 | 330 | 6.163 | 12,52 |
| 6208 2RS ENC INOX | 40 | 80 | 18 | 410 | 5.564 | 14,73 |
| 6209 2RS ENC INOX | 45 | 85 | 19 | 460 | 5.050 | 16,70 |
| 6210 2RS ENC INOX | 50 | 90 | 20 | 500 | 4.794 | 19,64 |
| 6211 2RS ENC INOX | 55 | 100 | 21 | 650 | 4.194 | 23,73 |
| 6212 2RS ENC INOX | 60 | 110 | 22 | 820 | 3.852 | 29,46 |
| 6213 2RS ENC INOX | 65 | 120 | 23 | 990 | 3.638 | 33,96 |
| 6214 2RS ENC INOX | 70 | 125 | 24 | 1040 | 3.424 | 36,01 |
| 6215 2RS ENC INOX | 75 | 130 | 25 | 1210 | 3.124 | 40,10 |

| Código | Agujero (B) | Diámetro (D) | Ancho (W) | Peso g | Velocidad Rotaciones/min. | Carga Estática Kn |
|-------------------|-------------|--------------|-----------|--------|---------------------------|-------------------|
| 6300 2RS ENC INOX | 10 | 35 | 11 | 57 | 14.250 | 2,82 |
| 6301 2RS ENC INOX | 12 | 37 | 12 | 64 | 12.900 | 3,40 |
| 6302 2RS ENC INOX | 15 | 42 | 13 | 86 | 11.600 | 4,42 |
| 6303 2RS ENC INOX | 17 | 47 | 14 | 160 | 10.300 | 5,67 |
| 6304 2RS ENC INOX | 20 | 52 | 15 | 180 | 9.050 | 6,96 |
| 6305 2RS ENC INOX | 25 | 62 | 17 | 270 | 7.100 | 9,33 |
| 6306 2RS ENC INOX | 30 | 72 | 19 | 390 | 6.100 | 13,34 |
| 6307 2RS ENC INOX | 25 | 80 | 21 | 500 | 5.550 | 15,55 |
| 6308 2RS ENC INOX | 40 | 90 | 23 | 670 | 4.900 | 20,46 |
| 6309 2RS ENC INOX | 45 | 100 | 25 | 870 | 4.300 | 26,19 |
| 6310 2RS ENC INOX | 50 | 110 | 27 | 1090 | 3.950 | 31,10 |
| 6311 2RS ENC INOX | 55 | 124 | 29 | 1390 | 3.425 | 38,87 |
| 6312 2RS ENC INOX | 60 | 130 | 31 | 1740 | 3.250 | 42,56 |
| 6313 2RS ENC INOX | 65 | 140 | 33 | 2100 | 2.990 | 49,10 |
| 6314 2RS ENC INOX | 70 | 150 | 35 | 2500 | 2.825 | 57,49 |
| 6315 2RS ENC INOX | 75 | 160 | 37 | 3000 | 1.600 | 62,61 |

2RS



ENC 6300 INOX

☉ CARACTERÍSTICAS TÉCNICAS

- Material: acero inoxidable.
- Juego radial standard.
- Protección en goma tipo 2rs.
- Lubricados

☉ CAMPOS DE APLICACIÓN

- Aplicaciones con alto grado de humedad

